



DESCRIPTION

The New Construction Mini Multiple Downlight are equipped with 1, 2, 5, 10 and 15 lamps. The miniaturized design, die-cast aluminum body, and high-performance acrylic diffuser provide uniform scientific light output for maximum visual comfort.

FEATURES


Revolutionary narrow recessed downlight available in slim trim or trimless. The simplified retrofit installation can be used in both new and existing spaces. Dimmable with a variety of commonly used drivers. Life Rated for 50,000 hours at 70% lumen maintenance. Easy installation for new construction and remodel applications.

SPECIFICATION

Optics: Low luminance: Spot optic, with ppti beam technology
 Material: Body and Heat sink: Die-cast aluminum, Reflector and Baffle: Thermoplastic
 Mounting: New construction installation or remodel installation
 Electrical: High efficiency electronic driver, rated at 50 000 hours
 Weight: 0.1 to 2.42lbs (0.05 to 1.1kg)
 Warranty: 3 year limited warranty.



DIMENSIONS



1x1 LAMP

L: 9 13/16" x W: 9 13/16" Cut-Out: 1 3/8" x 1 3/8"

1x2 LAMP

L: 9 13/16" x W: 9 13/16" Cut-Out: 1 3/8" x 2 1/2"

1x5 LAMP

L: 9 13/16" x W: 9 13/16" Cut-Out: 1 1/2" x 5 1/2"

2x5 LAMP

L: 15 5/16" x W: 9 13/16" Cut-Out: 1 1/2" x 10 3/4"

3x5 LAMP


L: 20 5/8" x W: 9 13/16" Cut-Out: 1 1/2" x 16"



TRIM OPTION



Trimmed



Trimless



IL-G401XA-X-NC Series



SERIES	LUMEN	CRI	CCT	DIMMING	INPUT VOLTAGE	TRIM	FINISH	REFLECTOR
IL-G4011A-01-NC	150lm	>80	3000K	Non-dimming	120V	Trimmed	White	White
IL-G4011A-02-NC	310lm	>90	4000K	TRIAC Dimming	277V	Trimless	Black	Black
IL-G4011A-05-NC	720lm		5000K	0~10V Dimming	120-277V		Silver	Chrome
IL-G4012A-10-NC	1450lm							Gold
IL-G4013A-15-NC	2200lm							

Last update: 2020

Due to continuous improvements, the information herein may be changed without notice



Impulse Lighting Inc.
www.impulselightingusa.com
12603 FM 529 Rd Houston TX
Phone: 855-315-365