

Catalog #	Type	Type
Project		
Comments		Date
Prepared by		

WARRANTY & LISTINGS

- cULus listed for damp and wet locations.
- Energy Star qualified.
- Title 24 compliant.
- Complies with RoHS (Restriction on Hazardous Substances) requirements.
- 5-year warranty of all electronics and housing.



Certification Information

2700K	3000K	4000K	5000K

FEATURES

- Available in 4000k (neutral white) color temperatures.*
- Long-life LEDs provide at least 70% of initial lumen output (L70) for 50,000 hours of operation.**
- Provides up to 4,530 nominal lumens.
- Color rendering index (Ra) > 80.
- Flat bar hangers available for ceiling grid mounting (order separately).
- Junction box is mounted on frame for easy wiring and driver access.
- Integral heat sink for heat disbursement.
- Tapered aluminum reflector with frosted lens.
- Input voltage = 120-277V (50-60Hz).
- Wattage = 40W or 52W
- 0-10V dimming.



ORDERING INFORMATION -Frames

Model	DESCRIPTION
IL- BL8CLED-40A	8" FRAME, 40 WATTS, FOR USE WITH BL8TCLD-40HZ-4K
IL- BL8CLED-52A	8" FRAME, 52 WATTS, FOR USE WITH BL8TCLD-52HZ-4K

ORDERING INFORMATION -TRIMS

IL- BL8TCLD-40HZ-4K	8" TRIM, 4000K, 3,090 LUMENS, FOR USE WITH BL8CLED-40A
IL- BL8TCLD-52HZ-4K	8" TRIM, 4000K, 4,530 LUMENS, FOR USE WITH BL8CLED-52A

MOUNTING ACCESSORIES

ZZ-BARHANGER-ARCHCAN-FLAT27"	FLAT BAR HANGER - 27", FOR ARCHITECTURAL CANS
------------------------------	---

Due to continuous improvements, the information herein may be changed without notice

DIMENSIONS

