

Catalog #	Type	Type
Project		
Comments		Date
Prepared by		

OPTIONS

- WM: Wall mount.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- UL listed for damp locations (0° – 50°C).
- Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes.
- Meets city of Chicago sign and plenum requirements.
- Certified to CEC under Title 20 Regulations.

HOUSING

- Premium-grade, extruded aluminum housing.
- Extruded aluminum trim assembly is easily detachable, providing accessibility for service or maintenance. Also available in optional white finish.
- Single or double face configurations.



Certification Information



ILLUMINATION

- Ultra-bright, energy efficient, long-lasting white LEDs provide uniform illumination.
- UV stabilized, silk screened acrylic panels provide consistent,

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Compatible with drywall or drop-thru ceiling mount installations.
- Wall mount capability optional.



ORDERING INFORMATION

ITEM NUMBER	No. of FACES	LETTER COLOR	HOUSING	BATTERY	OPTIONS	OPTIONS
IL-CARELZXTE	1 - Single Face	RW-Red on White	W-White	(blank)-AC-Only	WM - Wall Mount ¹	NA - Exit No Arrow S - NA - Stair No Arrow
	2 - Double Face		A-Aluminum	EM-Battery Backup		-DA - Exit Double Arrow -S-DA - Stair Double Arrow
						-RA ¹ Exit Right Arrow -S-RA ¹ - Stair Right Arrow LA ¹ - Exit Left Arrow -S-LA ¹ - Stair Left Arrow
						-LARA ² - Exit Left/Right Arrow -S-LARA ² - Stair Left/Right Arrow

Due to continuous improvements, the information herein may be changed without notice

DIMENSIONS

